

FLEXIBLE PV PANEL KIT

**ULTRA LIGHT** 

# 200Wp\*4







Ultra Light/Pcs

Bendable

Installation Costs



#### **IP68**

The system is capable of withstanding rain, water mist, splashes, and other water-related hazards; as well as suitable for different outdoor applications to ensure stable operation.



### **Ultra Light**

Lightweight frameless design, the weight is only 3.1 kg, which is up to 70% lighter than conventional glass module



# **Extreme Weather Resistant**

Organic composite encapsulation materials instead of heavy glass for lamination encapsulation, durable and weather resistant



# Flexibility and Durability

World leading non-glass impact resistant technology with bendable surfaces



### **Easy Installation**

Without traditional brackets and limitation of installation surface, it can save up to 50% of installation costs




#### **Certificates**

TUV Certificate IEC/EN 61215 IEC/EN 61730


# **Technical Parameters**

MODEL	FLEXIBLE PV PANEL ULTRA LIGHT 200W
MECHANICAL SPECIFICATIONS	
Solar Cell Type	Topcon
Number of Cells	54 pcs
Dimensions (WxHxD)	1154x899x2mm
Net Product Weight	3.1kg
Color	Black
Ingress Protection	IP68
Output Cable	TUV 4.0mm²
Wire Length	(+)500mm, (-) 500mm, or customized
Connector	MC4 compatible
ELECTRICAL SPECIFICATIONS	
Rated Peak Power (Pmax)	200W
Open Circuit Voltage (Voc)	37.5V
Short Circuit Current (Isc)	6.38A
Max Power Voltage (Vmp)	32.9V
Max Power Current (Imp)	6.08A
Module Efficiency	19.3%
Operating Temperature	~40°C to 85°C
Max System Voltage	1000V DC
Max Series Fuse Current Rating	15A
Power Tolerance	±3%
Standard Test Conditions	1000W/m², 25°C, AM1.5
Certificates	CE, REACH, WEEE, ROHS, IP





# **Packaging Information**



\*NOVGEN reserves the right of final interpretation. 202503\_V1\_EN









4 x 200Wn Solar Panel

8 x 2m MC4 Cable 3 x Y St

3 x Y Shaped Connect Se

1 x Labor Protection Glov





1 x Anti-dropping Rope

60 x UV-resistant Plastic Cable Tie 60 x Stainless Steel Cable Tie

1 x MC4 Wrench
\*Diagram for reference only



## NOVEEN

Call Us Email Website Add +86 755 27210648 sales@novgen-ess.com www.sunpura.de C503, Gaoxinqi Industrial Park Phase 1, Baoan District, Shenzhen, China

### VIDIS GmbH (European HQ)

Call Us
Cell Phone
Email
Website

+49 (0) 4051484048 +49 (0) 15170691704 support@vidis.com www.vidis.com

Add Rungedamm 37, 21035 Hamburg, Germany